



BOSS[®]

DIGITAL GLOSS OPP FILM

Digital Gloss Film

High quality OPP Single Side Laminating Film suitable for digitally produced media. Coated with a more aggressive adhesive for a better finish.

OPP Film is ideal for laminating menus, business cards, book covers and postcards.

- 50% higher adhesive strength to the printed medium than a standard film.
- The best adhesion to digital printing, dark backgrounds or dense inks.
- The best solution for the most difficult jobs, such as heavy weights, cardboard, sheet lamination and work with embossing.
- The same optical qualities and properties as standard Boss films.

PERFECT PARTNERS

• Digital film works well with all single sided laminators including:

- Matrix[®] Single Sided Laminators
- Matrix[®] Dual Sided Laminators

MATRIX[®]

MATRIX[®] DUAL

TECHNICAL SPECIFICATIONS

	DIGI-STICK THERMO GLOSS	DIGI-STICK THERMO GLOSS		
	24 DD 230	35 DD 230		
Properties Propiedades Propriétés	VALUES / VALORES X	VALUES / VALORES X	UNITS UNIDAD	TEST METH MET. ENSAYO
Thickness Espesor Épaisseur	24	35	μ	ASTM- E 252
	0,96	1,4	Mills	
	96	140	Gauges	
Yield Rendimiento Rendement	45,7	31,2	m ² /kg	ASTM D 4321
	32.105	21.907	ln ² /Lb	
Gloss Brillo Brillance	95	95	%	DERPROSA
Wetting Tension Tensión Superficial Tension Superficielle	36÷39	36÷39	Dynes/cm Dinas/cm	ASTM D 2578
C.O.F. Film/Film	0,4	0,4		ASTM D 1894
Application Temperature Temperatura de Aplicación Température d'application	105°-115 C°(221-239°F)	105°-115 C° (221-239 °F)	°C (°F)	
Lamination Strength Fuerza de Laminación Adhérence du Laminage (Not printed paper)	≥ 7,5 ≥ 1,71	≥ 10 ≥ 2,2	N/25mm Lb/Inch	ASTM D 882

The above information is based on conclusive test evidence and Vivid experience. We may refuse any responsibility arising from the use, handling or treatment of products after delivery and its guarantee is only related to the quality of the products, as specified on the transaction contract. The delivered raw and packaging materials have been manufactured following the current laws and any important change in the properties of them will be notified previously in order to be accepted by the customer.

/vividlaminating

@vividlaminating

/vividlaminating

Vivid Laminating Technologies Ltd

St Georges House, Whitwick Road, Coalville, Leicestershire LE67 3FA England

vivid-online.com

0845 1 30 40 50 sales@vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company.