Ace Adhesives Limited
Shenstone Drive
Northgate
Aldridge
WS9 8TP
Tel: 0044 (0) 1922 459393
Email: sales@aceadhesives.co.uk

Technical Data Sheet



PRODUCT IDENTIFICATION

PRODUCT NAME: DEV239

PRODUCT TYPE: VAE ADHESIVE STATUS: STOCK ITEM

DATA SHEET VERSION: 012

DATE OF ISSUE: 18th APRIL 2020

MANUFACTURER: Ace Adhesives Limited



TECHNICAL DATA

SOLIDS CONTENT: 51 - 56% Infra Red Moisture Analyser VISCOSITY: 3800 - 4400cPs Brookfield RVF 4/20/25°C USING TEMPERATURE: Ambient

DILUTION: Use neat as received

APPLICATION INFORMATION

MAIN USAGE: All applications where adhesion to difficult surfaces is required.

Recommended for casing-in of books, board laminating and

printed carton manufacture

MACHINE TYPES: All roller & pump fed casing-in lines. All high speed carton lines

where adhesive is wheel applied.

RUNNING SPEEDS: Dependant on machine type and compression time

SUITABLE MATERIALS: Coated & uncoated paper, board & bookbinding materials

ADDITIONAL INFORMATION: All ingredients meet the requirements of

FDA CFR21 175.105 Adhesives

PACKAGING DETAILS

PACK SIZES: 25Kg polythene bottles 1000Kg IBCs

PALLET SIZES: 1200mm x 800mm 1200mm x 1000mm

FULL PALLET WEIGHT (NETT): 600Kg (24 x 25Kg) 1000Kg

STORAGE: Store between 5 - 25°C. Storage outside of the suggested

temperature range could adversely affect the properties of the

adhesive









