

# UTACK HEXO FLOOR

## INDOOR VINYL

Self adhesive vinyl with a clear removable adhesive - Super Hexagon structured surface with an R10 anti slip rating, making Hexofloor the ideal material for fast and effective floor graphics and branding - no lamination required. Hexofloor can also be applied to any other smooth surface or board to create graphics with a difference.

### Technical Data

Description:	Self adhesive calandered monomeric soft-PVC
Thickness:	150 $\mu$ $\pm$ 10% (foil without embossing)
Color:	Digital white
Finish:	"Super Hexagon"
Adhesive type:	Waterbased semi permanent clear
Liner:	135 g/m <sup>2</sup> Siliconised Kraft
Dimensional stability MD:	$\leq$ 0,5mm- FINAT 14
Dimensional stability CD:	$\leq$ 0,5mm- FINAT 14
Adhesive strength:	7 $\pm$ 4N/25mm - FINAT TM 1, after 24 hours, adhered to stainless steel
Dimensions:	137 cm x 25 m other sizes on request
Fire behaviour:	Self extinguishing, adhered to stainless steel
Anti-slip certificate:	R 10/V-,-; DIN 51130 IFA

### Application

Usage:	Short term indoor advertising and promotion on floors. After printed directly useable. No lamination needed. **
Surfaces:	Flat floor surfaces

Recommended application temperature:	> 10°C
Product application temperature:	-20°C to 70°C
Durability:	Up to 3-4 years unprinted **
Shelf life at 23°C / 50% moisture:	2 years in original boxes *

\* Average Value

\*\* Under horizontal exposure, based on Central Europe Climate

### Guarantee

All CMYUK materials are subject to quality control, manufactured according to highest quality standards and warranted to be of merchantable quality. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable, but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. All specifications are subject to change without prior notice.