PaperTac™

White Matte

PaperTac™ White Matte is a premium coated paper with clear permanent adhesive, ideal for retail promotion, advertising, events, and more. Designed for exceptional print quality across a range of printers—including aqueous, latex/resin, and UV—this versatile media delivers stunning photorealistic prints, making it perfect for short-term applications and eco-conscious projects.

Engineered for durability, PaperTac™ White Matte features water-repellent and scratch-resistant properties, ensuring long-lasting indoor performance. Its clear permanent adhesive allows for easy mounting to rigid card substrates, eliminating the need for a flatbed printer when creating printed boards.

For brands and print professionals seeking a sustainable solution without compromising on quality, PaperTac™ White Matte delivers the perfect balance of performance and eco-responsibility.

140 Coated gsm Paper





Aqueous Latex/Resin UV



Clear Permanent Acrylic Adhesive

Widths up to 1250mm







APPLICATIONS

RETAIL PROMOTIONS
EVENT GRAPHICS
MOUNT TO BOARDS





PaperTac™

White Matte

TECHNICAL SPECIFICATION

PaperTac[™] is a high-quality 140gsm matte-coated paper designed for wide color gamut aqueous printers, and is also suitable for use on latex/resin, and UV printers. This versatile media is ideal for photorealistic prints, short-term advertising, and other eco-friendly applications. Its water-repellent and scratch-resistant properties ensure durability for indoor use.

Featuring a clear permanent adhesive, PaperTac™ can be easily mounted to rigid card substrates, allowing users to create printed boards without the need for a flatbed printer. It is backed by a 100gsm double-sided PE Kraft siliconized release liner, ensuring smooth handling and application.

PaperTac[™] is an eco-conscious solution, catering to the growing demand for sustainable print media without compromising on print quality and performance.

PaperTac White Matte is a Best-in-Class solution designed for easy recycling—both the paper face film and adhesive can be recycled together with no visual or adhesion issues. It achieves a 91/100 recyclability score using the CEPI Recyclability Test Method v2 (Oct 2022).

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

PRODUCT STRUCTURE

Film	Matte Coated Paper
Adhesive	Clear Permanent Water Based (Acrylic)
Release Liner	100 gsm 2 Sided PE Siliconised Kraft

PRODUCT CHARACTERISTICS

Film Thickness	140 gsm
Adhesive Layer	0.6 mil (14 _µ)
Outdoor Durability	Not Applicable
CEPI Recyclability Score	91/100 - Best In Class
Application Temperature	>41°F (5°C)
Service Temperature Range	41°F to 104°F (5°C to 40°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

30 Driver Road, Brampton, Ontario, L6T 5V2, Canada toronto@drytac.com Tel: +1 800.353.2883

USA

5401-B Eubank Road, Sandston, Virginia, 23150, USA customerservice@drytac.com Tel: +1 800.280.6013